



# fi-6110

### Color Duplex Desktop Scanner

## Get paperwork out of the way with this powerful desktop scanning solution

The Fujitsu fi-6110 scanner's small footprint and advanced feature set make it an ideal solution for decentralized scanning environments. With its true, 600-dpi optical resolution and dual-CCD cameras, it captures your documents' finest details in color, grayscale, and monochrome. What's more, it shares much of the advanced technology found in higher-end scanners, including a 50-sheet automatic document feeder (ADF) that accommodates a wide range of document sizes (2.1 in. x 2.9 in. to 8.5 in. x 14 in.), ultrasonic double-feed detection for greater security, and a Carrier Sheet function for feeding fragile or oversized (A3) documents. Plus at speeds up to 20 ppm (simplex) / 40 ipm (duplex) it quickly and efficiently transforms your paper documents into more manageable digital files. PaperStream IP and PaperStream Capture utilities are included with the Fujitsu fi-6110 scanner, which allow you to quickly and easily integrate it into your workflow.

#### **Fleet Management**

Scanner Central Admin provides IT departments an efficient way to manage medium to large scanner deployments. With remotely accessible fleet information, IT departments can now allocate resources effectively based on scan volume, consumable wear, depreciation schedules and maintenance expiration.

#### Help maximize uptime with service by Fujitsu.

The fi-6110 scanner includes a one-year Limited Warranty and is eligible for our Advance Exchange Program for fast up-time response and total peace-of-mind. For full details on the Limited Warranty and on all service programs, go to www.lmagingService.com or call (800) 626-4686.

#### **About Fujitsu Computer Products of America, Inc.**

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.

#### Fujitsu Computer Products of America, Inc.

http://us.fujitsu.com/fcpa 1250 East Arques Avenue Sunnyvale, CA 94085-5401 Sales: (888) 425-8228, Tech Support: (800) 626-4686 info@fcpa.fujitsu.com

Technical Spec	ifications				
Model		T fi 6110			
* * * *		fi-6110			
Scanner type		ADF (Automatic Doucment Feeder)			
Scanning Modes Image Sensor Type		Duplex / Simplex, Color / Grayscale / Monochrome			
Light Source		Color CCD (Charge Coupled Device x 2)			
3		White cold cathode discharge lamp			
Optical Resolution		600 dpi			
Output	Color (24 bit)			50 1 000 1 1 1000 1 19	
Resolution <sup>1</sup>	Grayscale (8 bi		50 to 600 dpi, 1200 dpi <sup>2</sup>		
Monochrome (		,			
Internal Video Processing		1024 levels			
Image Processing Functions		Auto color detection, Automatic page size detection, Automatic Rotation, Upper lower separation, Multi-image, Blank page skip, Error diffusion, Dither, Dropout color (R, G, B, None, Specified), Image Emphasis, Simplified DTC, Advanced DTC, Moire removal <sup>3</sup> , sRGB <sup>3</sup>			
Scanning Spee	ds				
Output (Letter/A4 size)4			Simplex	Duplex	
Color <sup>5</sup>	200 dpi & 300	dpi	20 ppm	40 ipm	
Grayscale <sup>5</sup>	200 dpi & 300	dpi	20 ppm	40 ipm	
Monochrome	200 dpi & 300		20 ppm	40 ipm	
ADF Capacity <sup>6</sup>	50 Sheets (letter/A4, 20 lb.) (Active loadable ADF)			20 lb.) (Active loadable ADF)	
, ,	ADF Minimum		2.1 x 2.9 in. (52 x 74mm)		
Document size	ADF Maximum		8.5 x 14 in. (L	,	
	Long Document			nd 8.5 x 125 in. <sup>7</sup>	
Paper Weight Normal		14 to 34 lb. (52 to 127g/m2) 0.06 to 0.15 mm			
(Thickness) A8 sheets		34 lb. (0.15 mm) only			
		IISB 2	SB 2.0 / USB 1.1 (B type connector)		
Physical Specifications			200 Z.O 7 GOD 1.1 (D type connector)		
· ·			100 to 240 VAC ± 10%		
Power requirements  Power consumption		Operating mode: 28W or less (Sleep mode: 5.36W or less)			
Dimensions (WxDxH) <sup>8</sup>		11.5 x 5.6 x 5.1 in. (292 x 143 x 130 mm)			
		6.61 lb. (3 kg)			
Weight					
		RoHS <sup>9</sup>			
Operating	Temperature			°F (5°C to 35°C)	
Environment	Relative humidi		20 to 80% (non-condensing)		
Driver Interface Included		PaperStream IP (TWAIN/ISIS)			
Bundled Software		PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, Scanner Central Admin Agent			
Included Items		AC Adapter, AC Cable, USB Cable, Carrier Sheet, Setup DVD-ROM, Documentation			
OS Support		Windows® XP, Windows Vista®, Windows Server® 2008, Windows® 7, Windows® 8, Windows Server® 2012			
Other Features		Ultrasonic Double Feed Detection Sensor, Long Document Scanning (125 in.) <sup>7</sup> , Carrier Sheet Function (Supports A3 and DL size documents			
Limited Warranty		One-Year Depot. Advance Exchange program also available; restrictions apply. For full details, visit www.lmagingService.com or call (800) 626-4686.			
Service Options		Post-Warranty: Advance Exchange; restrictions apply. Consumables: ScanAid™ kit. For full details, visit www.lmagingService.com or call (800) 626-4686.			
Part Number		PA03607-B065			

- 1 Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
- 2 Intel® Core™ i5 desktop processor 2.5 GHz or higher, 4 GB RAM is recommended
- 3 The ISIS driver does not support this function.
- 4 Actual scanning speeds are affected by data transmission and software processing times.
- 5 JPEG compressed figures.
- 6 Maximum capacity varies depending upon paper weight.
- 7 The scanning of documents that exceed 34 inches in length will be limited to using TWAIN at 200 dpi or less.
- 8 Excluding the ADF paper chute and stacker
- 9 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC)













