Take your office productivity to a new level.

Kodak
i100 Series Scanners

All the scanning performance and flexibility your busy office or department needs.

- Simplex (i150) and duplex (i160) models for color, bitonal and grayscale imaging

- Perfect Page Scanning with iThresholding delivers sharp, clean images without rescanning

- Renowned SurePath paper handling that minimizes jams

- Scans up to A3-size documents to handle your full workload

- 3-D ultrasonic multi-feed detection lets you scan with confidence

- Easy setup and operation

- Worldwide service and support for your peace of mind

TWAIN
Linking Images With Applications

ISIS

PerfectPage
now with
iThresholding

Kodak

Features and Benefits

Perfect Page Scanning with iThresholding:
Advanced image processing from Kodak allows you to scan even poor-quality documents and get great images. Image cropping and straightening happen at full scanning speed. We've virtually eliminated the need to rescan or change settings so that you can be more productive, automatically.

Competitive scanner

Perfect Page Scanning with iThresholding, only from Kodak

Exclusive SurePath paper handling is designed for smooth paper transport and virtually jam-free operation.

Flexible feeding capability: Get through workloads faster by scanning documents up to A4 length (297 mm/11.7 in.) in landscape mode. For more flexibility, the feeder handles documents up to 432 mm/17 in. (A3 length) in portrait mode.

Five output options: Color, bitonal, grayscale, simultaneous bitonal and grayscale and simultaneous bitonal and color.

Electronic Color Dropout: Suppress irrelevant red, green or blue backgrounds for efficient forms processing.

3-D multi-feed detection with ultrasonic technology lets you feed a wide variety of paper types and weights with confidence that you'll capture your images.

IEEE-1394 (FIREWIRE) interface allows for quick setup and speeds your images on their way. For your convenience, we also include the IEEE-1394 card and cable.

Small footprint and quiet operation: Both models scan large documents but are still small enough to fit easily on any desktop.

KODAK Capture Software, Lite installs in minutes and supports a range of scanning features for practically any office application. Easily upgradeable to the full version of Capture Software.

VRS Compatible for additional imaging options.

KODAK Service & Support: Our team of service experts is here for you around-the-clock, all over the world.

Specifications

Recommended Daily Volume	Up to 3,000 pages per day
Throughput Speeds (Landscape, Letter Sized, Bitonal, Grayscale, Color)	**Resolution** / **i150 (simplex)** / **i160 (duplex)** 150 dpi / 53 ppm / 53 ppm/106 ipm 200 dpi / 40 ppm / 40 ppm/80 ipm 300 dpi / 27 ppm / 27 ppm/54 ipm In simultaneous output mode*: **Resolution** / **i150 (simplex)** / **i160 (duplex)** 150 dpi / 53 ppm/106 ipm / 53 ppm/212 ipm 200 dpi / 40 ppm/80 ipm / 40 ppm/160 ipm 300 dpi / 20 ppm/40 ipm / 20 ppm/80 ipm *scanning with simultaneous output of bitonal and color, or bitonal and grayscale, images
Scanning Technology	Single Tricolor Plus CCD (i150); Dual Tricolor Plus CCD (i160) Grayscale output bit depth is 256 levels (8-bit) Color capture bit depth is 40-bit (10 bits per red, green, blue and black channels) Color output bit depth is 24-bit
Optical Resolution	300 dpi
Illumination	Single 2500 hour+ Xenon lamps
Output Resolution	75/100/150/200/240/300/400/600 dpi
Maximum Document Size	297 mm x 432 mm (11.7 in. x 17 in.)
Minimum Document Size	64 mm x 89 mm (2.5 in. x 3.5 in.)
Paper Thickness and Weight	Onionskin to card stock
Feeder	Automatic Document Feeder for continuous loading of up to 150 sheets of 60 g/m2 (16 lb.) paper
Multi-feed Detection	3-D multi-feed detection with ultrasonic technology
Connectivity	IEEE-1394 (FIREWIRE) Interface (card and cable included), 6-pin connector
Bundled Software	TWAIN and ISIS drivers; KODAK Capture Software, Lite
Imaging Features (in the scanner)	Perfect Page Scanning with iThresholding, Autocrop, Aggressive Crop, Deskew, Electronic Color Dropout, Orthogonal Rotation, Halftone Removal, Noise Removal, VRS Compatible
On-board compression	CCITT Group IV; JPEG or uncompressed output
File Format Outputs	JPEG (for color and grayscale images) TIFF (for bitonal images)
Warranty (US and Canada)	One year (3 months on-site, then 9 months mail-in)
Electrical Requirements	100-240 V; 50-60Hz
Environmental Factors	ENERGY STAR qualified scanners Mercury-free Xenon lamps Operating temperature: 15-30° C (59-86° F) Operating humidity: 15% to 76% RH
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <44 dB(A) Operating mode: <57 dB(A)
PC Configuration	Minimum: PENTIUM III 1 GHz processor, 256 MB RAM Recommended: PENTIUM IV 2.4 GHz processor, 512 MB RAM
Supported Operating Systems	WINDOWS 98SE, Me, 2000, XP
Approvals and Product Certifications	UL 60950 2000-1, C-UL CAN/CSA-C22.2 No. 60950-1-03, TUV EN 60950-1:2001, CE Mark, 47 CFR Part 15 Subpart B (FCC) Class B, ICES-003 Issue 3 Class B, EN 55022:98 Class B, EN 61000-3-2 Powerline Harmonics, EN 61000-3-3 Flicker, EN 55024, AS/NZS CICPR 22 Class B (C-Tick Mark), CNS 13438 Class B, VCCI Class B, CISPR 22 Class B
Consumables Available	Feed Module, Separator Module, Calibration Targets, Feeder Consumables Kit, Extra-Large Feeder Consumables Kit
Accessories	Replaceable imaging guides White imaging background accessory

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.

For more information visit: www.kodak.com/go/docimaging

• **Weight i150: 8.9 kg (19.8 lbs.)**
i160: 10.4 kg (23.0 lbs.)
• **Depth: 30.0 cm (11.8 in.)**
• **Width: 54.7 cm (21.5 in.)**
• **Height i150: 23.6 cm (9.3 in.)**
i160: 36.5 cm (14.4 in.)

i160 Scanner

i150 Scanner

We're here for you.
Kodak Service & Support

Innovation you can count on™