

Perfect for a wide variety of document capture, publishing and archiving needs.

- · Simplex (i55) and duplex (i65) scanners for color, black-and-white and grayscale imaging
- · Renowned image quality from Kodak with Perfect Page Scanning with iThresholding
- · Fast scanning at up to 32 pages—or up to 64 images—per minute
- · Automatic document feeder for easy scanning of documents up to 863 mm (34 in.) long
- · Built-in flatbed for convenient scanning of delicate or bound materials
- · Easy setup and operation with bundled drivers and a robust suite of software, including KODAK Capture Software, Lite
- · Dual connectivity: USB 2.0 (card and cable included) and SCSI-2
- · Worldwide service and support for your peace of mind















Features and Benefits

Fast scanning: Finish your workload quickly with the automatic document feeder.

Built-in flatbed scanning: Excellent for handling exception documents or bound materials.

Color, black-and-white or grayscale: Get the image types you need, when you need them, including simultaneous output of bitonal and color, or bitonal and grayscale images.

Ready, set, scan:

- · Simplified drivers for fast-start installation
- Connectivity for two interfaces: USB 2.0 (card and cable included) and SCSI-2
- · Bundled software lets you begin scanning right away:
- KODAK Capture Software, Lite, installs in minutes and helps automate your workflow for maximum performance. It allows scanning, viewing and storing of images in standard batch output formats, for practically any workgroup application. And it's easily upgradeable to the full version of Capture Software.
- READIRIS Pro Corporate Edition provides key functions for locating textual information fast, including multi-page optical character recognition (OCR) and direct scanning to searchable PDF files.
- KOFAX CAPIO for KODAK Scanners (demo version) is an easy-to-use personal filing and retrieval system.
- CAPTIVA QuickScan PRO (demo version) offers image capture functionality and customization features.

Autocrop and deskew: Automated scanning functions help you get through your workload fast.

User-replaceable wear parts: Stay up and running with snap-in parts.

Flexible color dropout: Improve OCR and text recognition by eliminating unwanted background color on your forms. Many colors can be "dropped out" by adjusting the red, green or blue channels via software.

KODAK Service & Support helps you stay up and running

KODAK Service & Support provides peace-of-mind coverage with more than 2,000 certified field engineers worldwide. Plus a global network of parts and distribution, exceptional on-site and help desk service, and a variety of service plans to fit the way you work. And it all comes with customer satisfaction ratings that are consistently above 95%. With KODAK Service & Support, the help you need is always close at hand.



We're here for you.
Kodak Service & Support

Specifications

Recommended daily volume	Up to 1,500 pages per day			
Throughput speeds	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	i55	i65	
bagpar specas		.00	.00	
(Portrait, A4, USB 2.0)	Color 150 dpi resolution	25 ppm	25 ppm/50 ipm	
ppm = pages/minute (simplex)	Grayscale 200 dpi resolution	32 ppm	32 ppm/64 ipm	
ipm = images/minute (duplex)	Bitonal 200 dpi resolution	32 ppm	32 ppm/64 ipm	
	Bitonal 200 dpi fixed threshold	36 ppm	36 ppm/72 ipm	
Scanning technology	i55: single CCD			
	i65: dual CCD			
	Grayscale output bit depth is 256	6 levels (8-bit)		
	Color capture bit depth is 48-bit			
	Color output bit depth is 24-bit			
Optical resolution	600 dpi			
Illumination	Cold cathode fluorescent lamp			
Output resolution	75, 100, 150, 200, 240, 300, 400 and 600 dpi			
Maximum document size	Flatbed: 215 x 297 mm (8.5 x 11.7 in.)			
	ADF: 215 x 863 mm (8.5 x 34 in.)			
Minimum document size	Flatbed: less than 25 x 25 mm (1x1 in.)			
	ADF: 94 x 140 mm (3.7 x 5.5 in.)			
Paper thickness and weight	Flatbed: From onionskin up to 38 mm (1.5 in.) thick bound materials			
	ADF: 16 to 28 lbs. (60 to 105 g/m²)			
Feeder	Automatic document feeder for loading of up to 75 sheets of 60 g/m² (16 lb.) paper			
Multi-feed detection	Via length detection			
Connectivity	SCSI-2 Interface: HD50 (50-pin) connectors			
	USB 2.0 (card and cable included)			
Bundled software	TWAIN and ISIS drivers; KODAK Capture Software, Lite;			
		READIRIS Pro Corporate Edition; KOFAX CAPIO for KODAK Scanners (demo version); CAPTIVA QUICKSCAN PRO (demo version)		
Imaging features	Perfect Page Scanning with iThresholding, autocrop, aggressive crop, deskew,			
(in the scanner)	electronic color dropout, halftone removal, noise removal			
Compression	CCITT Group IV; JPEG or uncompressed output			
File format outputs	JPEG (for color and grayscale images)			
(from bundled drivers)	TIFF (for bitonal images)			
Warranty (U.S. and Canada)	One-year warranty			
Electrical requirements	100-240 V; 50-60 Hz; universal power supply included			
Power consumption	i55 i65			
·	Running: ≤30W ≤35	W		
	ENERGY STAR: 8W 8V	V		
Environmental factors	ENERGY STAR qualified scanners	6		
	Operating temperature: 10–35° C (50–95° F)			
	Operating humidity: 20–85% RH			
Acoustical noise (operator	Standby mode: 20.6 dB(A)			
position sound pressure level)	Operating mode—Flatbed: 53.5 dB(A),			
	Operating mode—ADF: 47.5 dB(A)		
Minimum PC configuration	1 GHz processor, 512 MB RAM			
Supported operating systems WINDOWS 98SE , Me, 2000, XP				
	(only WINDOWS 2000 and WIN			
Approvals and product	UL/C-UL, TUVR/GS, CE, C-Tick, VCCI Class B, BSMI Class B,			
certifications				
	EN 61000-3-2 Powerline Harmo		0-3-3 Flicker	
Consumables available	Feed module (2 sets of 2 include	d in the box)		

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.



As an ENERGY STAR' Partner, Eastman Kodak Company has determined that these products meet ENERGY STAR' guidelines for energy efficiency. Height: 199 mm (7.8 in.)
 Width: 567 mm (22.3 in.)
 without output tray
 833 mm (32.8 in.)
 with output tray
 Depth: 350 mm (13.8 in.)
 Weight: i55—6.7 kg (14.8 lbs.)

i65-7.5 kg (16.6 lbs.)



For more information visit: www.kodak.com/go/docimaging

Eastman Kodak Company, Document Imaging, Rochester, NY 14650 1-800-944-6171 Kodak Canada, Inc., Toronto, Ontario M6M 1V3 1-800-465-6325 Kodak Gmbh Hedelfingerstr 60, 70327 Stuttgart, Germany EAMER-DI-Capture@kodak.com Kodak (Australasia) Pty. Ltd. North Ryde NSW 2113 Australia 61-2-9870-4224 Kodak (Hong Kong) Limited North Point, Hong Kong 07021 852-2654-9330 Kodak Japan Limited, Tokyo, Japan 81-3-5540-2270 jp-di-mktg@kodak.com Kodak de Mexico Mariano Otero 408 Guadalajara, Mexico (52) (33) 3818-6598 For other areas outside the U.S.A., call+1-585-722-9287

