MECHANICALLY PERFECT

PERFECT PERFORMANCE



SB 4000

- Ideal for back-office use
- High capacity and throughput in a compact footprint
- Voiding and endorsing options
- Codeline reading, imaging and sorting



The Seac Banche SB 4000 is suitable for data capture and document imaging requirements based on checks and financial documents such as credit transfer slips, travellers cheques, utility bills and other vouchers.

This peripheral unit combines the complete document processing capabilities of the internationally successful RDS 3000 reader scanner with the high throughput and capacity of a small reader sorter, within a much smaller footprint. These features make it ideal for a daily workload of several thousand documents in back-office applications, with an attractive price/performance ratio and surprising versatility.

Depending on processing requirements and document size, the basic **SB** 4000 can achieve a throughput up to 100 documents per minute, while the enhanced version **SB** 4500 can double the performance reaching up to 200 dpm.



SB 4000: standard speed 433 mm (17")/sec SB 4500: high speed 866 mm (34")/sec

PAPER HANDLING

Automatic document feeder with a capacity of up to 400 documents

Double feed control (IR standard, Ultrasound optional)

Three output stackers: capacity approx. 200 + 200 + 25 (reject) documents

DOCUMENT SPECIFICATIONS

Width: 100 to 210 mm (3.94" to 8.27") Height: 52 to 104 mm (2.05" to 4.09") Weight: 70 to 140 g/sqm (18.7 to 37.3 lbs)

CODELINE READING

MICR: magnetic fonts CMC7 and E13B

OCR (optional): optical fonts OCR-A alfanumeric, OCR-B alfanumeric. E13B

Barcode (optional): Interleaved 2 of 5, Code 39, Code

OCR/Barcode reader available with USB 2.0 interface only.

Barcode reading available at standard speed only.

IMAGE CAPTURE

SB 4000: up to 3 images in one pass (front, rear, front with red dropout) at standard speed SB 4500: front & rear images in one pass at high speed

200 x 200 dpi or 100 x 100 dpi 256 or 16 grey levels

IMAGE FORMAT

Bitmap, Jpeg, Tiff, G4 (B/W)

INTERFACE

USB 2.0

API SOFTWARE TOOLS

Designed for Microsoff[®] Windows[®] XP

Designed for MS Windows XP Available for MS Windows 2000, 95/98/ME Vista Compatible

DIMENSIONS

Length: 495 mm (19.5") Width: 265 mm (10.4") Height: 240 mm (9.4") Weight: 11 Kg (24.3 lbs)

COMPONENT

Antifraud feature by UV light - (No transport speed reduction)

ADDITIONAL FEATURES

Rear Inkjet Printer (optional)

Programmable endorser, application controlled Line of data can extend to full width of document


Front or Rear Stamp (optional)

Roll-on stamp with inking roller Maximum dimensions: $47 \times 18.5 \text{ mm} (1.8 \times 0.7")$ Front and rear stamp are alternative to one another

Duty Cycle

Daily Duty Cycle 20.00 documents Life Cycle 40 millions document





Via Francesco Petrarca, 14 - 50041 Calenzano (FI), Italy Tel.: +39 055.8870700 - Fax: +39 055.8873646

 $E. Mail: info@seacbanche.com - Web \ site: www.seacbanche.com \\$